NOTES:

- THIS DRAWING DESCRIBES THE FUELAB 414xx SERIES ELECTRONIC FUEL PUMP. UNLESS OTHERWISE SPECIFIED, ALL VIEWS ARE MODELS 41401-c, 41402-c OR 41403-c.
- FEATURES INCLUDE:
 - THREE PHASE DC BRUSHLESS MOTOR WITH NEODYMIUM MAGNETS

 - INTEGRATED ELECTRONICS WITH SPEED CONTROL
 WET MOTOR DESIGN, WITHOUT DYNAMIC SHAFT SEALS
 BILLET ALUMINUM, STAINLESS STEEL CONSTRUCTION
 - WITH FLUOROSILICONE SEALS
 - STANDARD T-BOLT STAINLESS STEEL BRACKETS INCLUDED
- FUEL COMPATIBILITY INCLUDES: - GASOLINE (PUMP OR RACE)
 - METHANOL
 - ETHANOL (INCLUDING E85)
 - DIESEL


UNIQUE SERIAL NUMBER DOES NOT CONTAIN DIRECT INFORMATION IN DETERMINING MODEL NUMBER. CONTACT FUELAB FOR DETERMINATION OF MODEL NUMBER BASED ON SERIAL NUMBER.


- TWO (2) T-BOLT STAINLESS STEEL BRACKETS, O-RINGS, INSTRUCTIONS AND PERFORMANCE CERTIFICATION INCLUDED, BAGGED SERPARATELY FROM PUMP.
- 8-32 VOLT OPERATING RANGE, USE ONLY 12 VOLT (6 CELL LEAD ACID BATTERY) VEHICLE SYSTEMS WITH OR WITHOUT CHARGING SYSTEM, OR 24 VOLT (12 CELL LEAD ACID BATTERY) VEHICLE SYSTEMS WITHOUT CHARGING SYSTEM.





MODEL 41404-c SAME AS 41403-c, EXCEPT HAVING EXTERNAL BYPASS VALVE WITHIN OUTLET CAP. MAXIMUM PRESSURE RATING FOR MODEL 41404-c IS A DEAD HEAD CONDITION (ZERO FLOW). ALL OTHER PUMP MODELS REQUIRE BYPASS REGULATOR OR RELIEF VALVE TO AVOID OVER-PRESSURE OPERATING CONDITION.

- REFERENCE DRAWING 1100202A1 FOR ASSEMBLY INSTRUCTIONS.
- SEE TABLES BELOW FOR DETERMINATION OF DESIRED MODEL NUMBER










UNLESS OTHERWISE SPECIFIED:	- Turlar	
INTERPRET DWG PER ANSI Y14.5 DIMENSIONS ARE IN INCHES	FUELAB COllinsville,	Illinois
TOLERANCES:	TITLE:	
FRACTIONAL:±1/64" ANGULAR: ± 1/2°		
DECIMALS:	ELECTRONIC FUEL P	UMP
.X±.1 .XX±.03 .XXX±.010 128 .		•
SURFACE FINISH OR BETTER	414xx SERIES	
BREAK ALL SHARP EDGES .010 MAX		
REMOVE ALL BURRS	SIZE DWG. NO.	REV
THIRD ANGLE PROJECTION	C 110020100	С
DO NOT SCALE DRAWING	SCALE: 1/1 WEIGHT: 2 / I D SHEET:	100

MODEL SELECTION TABLE


MODEL	FLOW RATING, AT 13.5v	FLOW RATING, AT 13.5v	MAX. PRESSURE
41401-c	125 GPH AT 45 PSI	473 LPH AT 3 BAR	125 PSI (8.5 BAR)
41402-c	145 GPH AT 45 PSI	549 LPH AT 3 BAR	100 PSI (6.8 BAR)
41403-c	200 GPH AT 20 PSI	750 LPH AT 1.5 BAR	80 PSI (5.5 BAR)
41404-c	200 GPH AT 20 PSI	750 LPH AT 1.5 BAR	30 PSI (2.1 BAR)


COLOR CODE, c

С	SLEEVE COLOR	CAPS COLOR
1	BLACK	BLACK
2	RED	CLEAR
3	BLUE	CLEAR
4	PURPLE	CLEAR
5	GOLD	BLACK
6	GREEN	CLEAR



ISOMETRIC VIEW SCALE: 1/2









SCALE: 1/1 WEIGHT: 2.4 LB SHEET: 2 OF 5

DO NOT SCALE DRAWING











SCALE: 1/1 WEIGHT: 2.4 LB SHEET: 3 OF 5

DO NOT SCALE DRAWING











DO NOT SCALE DRAWING

SCALE: 1/1 WEIGHT: 2.4 LB SHEET: 5 OF 5

6