NOTES:

- THIS DRAWING DESCRIBES THE FUELAB MODEL 253xx SERIES IN-TANK FUEL PUMP KIT.
- FEATURES INCLUDE:
 - THREE PHASE DC BRUSHLESS SCREW PUMP WITH TURBINE PUMP
 IN-TANK PUMP CONFIGURATION FOR EASY INSTALLATION
 EXTERNAL DC BRUSHLESS CONTROLLER WITH PWM SPEED CONTROL
 THREE WIRE BULKHEAD FEEDTHRU WITH TEFLON INSULATION

 - IN-TANK STRAINING FILTER
- **FUEL COMPATIBILITY INCLUDES:**
 - GASOLINE (PUMP OR RACE)
 - METHANOL
 - ETHANOL (INCLUDING E85)
 - DIESEL

UNIQUE SERIAL NUMBERS DO NOT CONTAIN DIRECT INFORMATION IN DETERMINING MODEL NUMBER. CONTACT FUELAB FOR DETERMINATION OF MODEL NUMBER BASED ON SERIAL NUMBER.


- INSTRUCTIONS AND PERFORMANCE CERTIFICATION INCLUDED, BAGGED SEPARATELY FROM PUMP. REFERENCE SUBSEQUENT SHEETS FOR FULL KIT CONTENTS OF THE VARIOUS AVILABLE MODELS.
- 8-16 VOLT OPERATING RANGE, USE ONLY 12 VOLT (6 CELL LEAD ACID BATTERY) VEHICLE SYSTEMS WITH OR WITHOUT CHARGING SYSTEM.
- SYSTEM REQUIRES BYPASS REGULATOR OR RELIEF VALVE TO AVOID OVER-PRESSURE OPERATING CONDITION. SYSTEM REQUIRES 20 AMP RELAY AND FUSE. ADDITIONAL PLUMBING REQUIRED FOR OUTLET FLOW.





SEE TABLE BELOW FOR DETERMINATION OF DESIRED MODEL NUMBER. MODELS 25304 AND 25314 HAS ADDITIONAL 6mm OUTLET FOR USE WITH JET PUMP (EDUCTOR) SYSTEM. BOTH OUTLETS CONTAIN CHECK VALVE. ALL OTHER PUMPS DO NOT HAVE BUILT IN CHECK VALVES.


MODEL SELECTION TABLE

MODEL	OUTLET TYPE	FLOW RATING, AT 13.8v	MAX. PRESSURE	SPECIAL FEATURES
25301	-6AN	92 GPH AT 45 PSI (350 LPH AT 3.0 BAR)	125 PSI (8.6 BAR)	
25302	5/16" SAE	92 GPH AT 45 PSI (350 LPH AT 3.0 BAR)	125 PSI (8.6 BAR)	
25303	3/8" SAE	92 GPH AT 45 PSI (350 LPH AT 3.0 BAR)	125 PSI (8.6 BAR)	
25304	9mm BARBED	92 GPH AT 45 PSI (350 LPH AT 3.0 BAR)	125 PSI (8.6 BAR)	AUX 6mm BARB SIPHON
25311	-6AN	132 GPH AT 45 PSI (500 LPH AT 3.0 BAR)	125 PSI (8.6 BAR)	
25312	5/16" SAE	132 GPH AT 45 PSI (500 LPH AT 3.0 BAR)	125 PSI (8.6 BAR)	
25313	3/8" SAE	132 GPH AT 45 PSI (500 LPH AT 3.0 BAR)	125 PSI (8.6 BAR)	
25314	9mm BARBED	132 GPH AT 45 PSI (500 LPH AT 3.0 BAR)	125 PSI (8.6 BAR)	AUX 6mm BARB SIPHON














REFERENCE 110021300, 120020100, AND 141020100 FOR EXTRA DETAILS INCLUDING DIMENSIONS, PERTAINING TO INCLUDED MODELS DETAILS INCLUDING DIMENSIONS, PERTAINING TO INCLUDED MODELS



6

